

## 906-116 Stainless Steel Face Vent Trim Installation Instructions Mazda MX5

440 Rutherford St. Goleta, CA 93117 1-800-642-8295 • FAX 805-692-2525 • www.MossMiata.com



Kit Contents: Four Vent Rings and Instructions

## You will need:

Soft non-abrasive cloth

## **Fitting Time:**

10 minutes total

- 1. Peel off the protective plastic covering from front of vent ring.
- 2. Clean all four plastic dashboard vents before installation.

- 3. Carefully peel the backing material away from the adhesive on the back of the vent ring. Avoid touching the glue.
- 4. Move the vent 'eyeball' to the straight ahead position, offer up the ring with one hand while ensuring with the other that the eyeball moves freely. Press very gently to just hold the ring in place, and check for full movement again. Remove and reposition if necessary. When you are happy with the fit, press firmly and evenly on the ring. Wipe with a soft cloth,
- 5. To preserve the surface finish, do not clean with abrasive cleaners or materials.

Although every effort has been made to ensure the accuracy and clarity of this information, any suggestions that you may have that will improve the information (especially detailed installation notes and photos) are welcome. These instructions were developed and written by Moss Technical Support. If you have any questions or difficulties with your installation of this product, telephone 800-667-7872 between 7:00 a.m. and 4:00 p.m., Pacific Time for assistance.

Moss Motors, Ltd. 440 Rutherford Street, Goleta, California 93117 In the US & Canada Toll Free (800) 667-7872 LOCAL (805) 681-3400 FAX (805) 692-2510



Moss Europe Ltd. Hampton Farm Industrial Estate Hampton Road West, Hanworth Middlesex, TW13 6DB In the UK: 020-8867-2020 FAX:- 020-8867-2030